

Material Safety Data Sheet

**HUT ULTRA GLOSS PLASTIC POLISH**

**SECTION I: CONTACT INFORMATION**

• <b>Manufacturers name:</b>	HUT Products
• <b>Address:</b>	4502 State Road J, Fulton, MO 65251
• <b>Emergency telephone number:</b>	1-800-547-5461
• <b>Information telephone number:</b>	1-800-547-5461
• <b>Date prepared:</b>	06-22-98
• <b>Prepared by:</b>	Fayette Environmental Services, Inc.

**SECTION II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

• <b>Hazardous components:</b>	64742-54-7 Paraffinic Distillate ~1 - 16%
	64742-85-0 Paraffinic Distillate (Dewaxed) ~1 - 16%

**SECTION III: PHYSICAL/CHEMICAL CHARACTERISTICS**

• <b>Boiling point:</b>	95°C
• <b>Specific gravity:</b>	1.09
• <b>Vapor pressure:</b>	Undetermined
• <b>Melting point:</b>	Undetermined
• <b>Vapor density:</b>	Undetermined
• <b>Evaporation rate:</b>	Undetermined
• <b>Solubility in water:</b>	Miscible
• <b>Appearance:</b>	White liquid
• <b>Odor:</b>	Slight odor

**SECTION IV: FIRE AND EXPLOSION HAZARD DATA**

• <b>Flash point:</b>	> 100°C (PMCC)
• <b>Auto-ignition temperature:</b>	Undetermined
• <b>Extinguishing media:</b>	Water fog or spray/CO2/Dry chemical/Foam
• <b>Unsuitable extinguishing media:</b>	None known
• <b>Unusual fire hazards:</b>	None known

**SECTION V: REACTIVITY DATA**

• <b>Stability:</b>	Stable
• <b>Conditions to avoid:</b>	As with any product, any unintended use should be avoided
• <b>Incompatibility (materials to avoid):</b>	None known
• <b>Hazardous decomposition byproducts:</b>	Thermal breakdown under very high heat conditions may evolve traces of the following decomposition byproducts: carbon oxides, traces of incompletely burned carbon compounds, silicon dioxide, formaldehyde.
• <b>Hazardous polymerization:</b>	None known/Will not occur
• <b>Conditions to avoid:</b>	As with any product, any unintended use should be avoided

**SECTION VI: HEALTH HAZARD DATA**

**Route(s) of Entry:**  
 • Inhalation:  
 • Skin:  
 • Ingestion:  
 • Carcinogenicity:  
 • Signs and symptoms of exposure:  
 • Medical conditions generally aggravated by exposure:  
**Emergency and First Aid Procedures:**  
 • Eye contact:  
 • Inhalation:  
 • Skin:  
 • Ingestion:  
 • Hazardous components:

Based on similar product testing, vapors generated at high temperatures may cause mild irritation of the mucous membranes of the upper respiratory tract.  
 A single prolonged exposure (24 to 48 hrs) may cause mild irritation. No more than slightly toxic if swallowed  
 None known  
 Irritation as noted above  
 None known  
 Flush with water.  
 Remove victim to fresh air.  
 Wash with soap and water.  
 Do not induce vomiting. Consult physician.  
 64742-54-7 Paraffinic Distillate ~1 - 16%  
 64742-65-0 Paraffinic Distillate (Dewaxed) ~1 - 16%

**SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE**

• Steps to be taken in case material is released or spilled:  
 • Waste disposal method:  
 • Precautions to be taken in handling and storage:  
 • Other precautions:

Soak up with appropriate sorbent material.  
 Dispose of according to federal, state, and local regulations  
 None known  
 None known

**SECTION VIII: CONTROL MEASURES**

**Ventilation**  
 • Local exhaust:  
 • Special:  
**Protection**  
 • Protection of hands:  
 • Eye protection:  
 • Other protective clothing or equipment:  
 • Work/Hygienic practices:

Use suitable respiratory protection device in case of insufficient ventilation  
 None known  
 Impervious gloves  
 Safety glasses  
 None known.  
 General protective and hygienic measures and personal protective equipment