



## WOOD WAX FINISH CLEAR EXTRA THIN

Finish for oily and resinous hardwoods!



1101 Clear Satin



### PRODUCT DESCRIPTION

Clear wood finish that uniquely combines the advantages of natural oils and waxes in one product.

Osmo Wood Wax Finish Clear Extra Thin is stain-resistant, water-repellent and abrasion-resistant and results in a surface that is pleasant to the touch

In comparison to conventional finishes, the use of plant ingredients creates a more even colour and more harmonious appearance.

Simple application – without primer or intermediate sanding – this saves time and money.

Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant against wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots.

The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

### RECOMMENDED USE

Osmo Wood Wax Finish Clear Extra Thin is suitable for the protection of wood in indoor areas: wall and ceiling panelling, wooden flooring, furniture and toys. Due to its water-repelling qualities, also especially well suited to the use in wet rooms (kitchens, baths, swimming pools etc.). Osmo Wood Wax Finish Clear Extra Thin is also particularly suited to the clear treatment of hardwoods rich in extractives, such as Meranti, Wenge, Merbau etc.

### CONTAINS

Based on natural plant oils and waxes (sunflower oil, soya oil, thistle oil, carnauba wax and candelilla wax), paraffin, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). Complies with Environment Canada VOC regulations (SOR/2009-264). Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.85-0.87 g/cm<sup>3</sup>

Viscosity: 39-43s DIN EN ISO 2431/3 mm, liquid

Odour: faint/mild, after drying odourless

Flash point: >60°C acc. DIN EN ISO 2719

### STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 18%).

Osmo Wood Wax Finish Clear Extra Thin is ready to use. Do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler).

If possible, please apply the first coat to all sides before installation.

Sand wood surfaces carefully. Begin with coarse sandpaper – final sanding work for flooring 120-150, for furniture P220-240. Before oiling the surface, remove sanding dust with a broom or vacuum cleaner.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.



## DIRECTIONS FOR USE

Osmo Wood Wax Finish Clear Extra Thin can be brushed, wiped, dipped or sprayed in an enclosed unit. Apply evenly along the wood grain with Osmo Flat Brush or a lint-free cloth (e.g. for furniture).

1<sup>st</sup> coat: apply thinly. Allow to dry for approx. 30 minutes under good ventilation. Wipe away any excess product. Reapply to unsaturated areas.

2<sup>nd</sup> coat: apply thinly. Allow to dry for approx. 30 minutes under good ventilation. Wipe away any excess product.

Recommended number of coats: one coat for furniture / two coats for flooring.

For renovation works, one coat applied to the clean and dry surface is usually sufficient.

## CLEANING OF TOOLS

With Osmo Brush Cleaner and Thinner (free of aromatic compounds).

## DRYING TIME

Approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

## COVERAGE

1 litre covers approx. 24 m<sup>2</sup> with one coat.

Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

## NOTE

Oils enhance the natural tone of wood (permanent wet effect). Applying the product too generously and insufficient ventilation lead to delays in drying time.

Caution: Apply max. one coat thinly to cabinet interiors and drawers with a cloth.

## HAZARD STATEMENTS



### CAUTION READ INSTRUCTIONS BEFORE USING

**DANGER OF COMBUSTION.** Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Use only in a well-ventilated area. Keep away from flames or sparks. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

**FIRST AID TREATMENT.** Contains aliphatic hydrocarbons. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

1101 Clear Satin

## CAN SIZES

750mL; 125mL

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 09/18