










FINISHING OPTIONS COMPARISON CHART

NAME	WHAT IT DOES	BENEFITS
Craft Coat Wood Finish CC-FIN-60Z 	Craft Coat is a one-component linseed oil modified waterborne urethane. It self cross-links when exposed to oxygen to develop an extremely durable film that exhibits outstanding scuff, mar and impact resistance.	Very durable Will not yellow over time Very little odour Dries quickly Great for use on exotic, dense and oily woods Provides depth and gloss
Aussie Oil PKSWAUS2 	Aussie Oil is formulated as a fusion mixture of hard shellac and oil, which when you apply to wood, traps oil in the matrix of the hard shellac. It gives wood a finish with a hard, bright, high gloss. It brings out depth in wood, making the grain pop.	Hard, high gloss finish
EEE Ultra Shine Polish PKSWEEE 	EEE Ultra Shine Polish is used as a final sanding step before applying your finish. It is a wax that contains Tripoli powder (an ultra-fine abrasive), which enhances the effects of sanding. It is NOT a finish in itself - use a wax based finish over top of it (ex. Shellawax) at high speed.	Used for both wood and plastics Eliminates sanding marks Greatly enhances the effects of sanding Brilliant shine and blemish free surface
Shellawax Liquid PKSWAXL1 	Shellawax is a liquid friction polish made for use on a wood lathe. The hardener in the polish is activated by heat generated during application, which fuses it to raw wood. Once the surface is dry, a cross-linking process in the finish begins (approx. 3 weeks to complete). It provides a hard, durable finish, resistance to marks from water, alcohol and heat.	Non-toxic finish Super easy to use One application Dries almost instantly Durable finish
Hut PPP Bar Combo HUT-PPP-COM 	The Hut PPP Bar Combo is a two-step finishing process for wood. The bars work together to remove fine scratches. Heat generated from application melts the wax into the surface of the wood. Includes a satin gloss bar (brown) and a high gloss bar (cream).	Ready-to-use finish No drying time Fast, durable finish
Hut Ultra Gloss Plastic Polish HUT-UG-POL 	Hut Ultra Gloss is a polish for plastics which removes scratches on almost any plastic surface. It can be used with a buffer, hand finishing, or lathe polishing.	Works on hard and soft plastics Gives plastics a glass-like finish
Mylands High-Build Friction Polish MYPOL 	Mylands is a quick building friction polish that is applied directly on the lathe. It provides a high gloss finish which brings out the natural beauty of wood.	Quick building High gloss finish with little effort Dries almost instantly
PSI Gloss Sealer PKFRICT3 	PSI Gloss Sealer is a liquid sealer designed to seal in the sap and resins from species of wood that tend to sweat after a period of time. It is a great first coat on your project regardless of the final finishing step.	Seals in sap and resins Gloss finish
Super Gloss Friction Polish PKFRICT2 	Super Gloss friction polish is a lacquer based finish that is applied to a project while still turning on a lathe. It can be applied over semi-gloss or directly onto tight grained woods. It seals, fills, and preserves your work.	Contains no waxes or oils Durable, rock-hard finish Gloss finish Dries instantly on the lathe